

Printing date 23.11.2021 Revision: 23.11.2021 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Aerosol diverse Farbtoene NC Spezial · (Article number) product ID.: REZ10 · 1.2 Relevant identified uses of the substance or mixture and uses advised against • Sector of Use SU21 Consumer uses: Private households / general public / consumers · Application of the substance / the mixture: painting · Uses advised against No further relevant information available.  $\cdot$  1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.: +49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0001 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms

· Signal word Danger

GHS07

GHS02

• *Hazard-determining components of labelling:* acetone

(Contd. on page 2)

Page 1/9

GB

Printing date 23.11.2021

Revision: 23.11.2021

<b>Trade name:</b> A	Aerosol diverse Farbtoene NC Spezial
	(Contd. of page 1)
n-butyl ace	etate
• Hazard sta	utements
H222-H22	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
• Precaution	nary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P305+P35	51+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P31	
P410+P41	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
<ul> <li>Additional</li> </ul>	l information:
Without ac	lequate ventilation, explosive atmosphere/gas mix may be created.
Warning!	Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
· 2.3 Other	hazards
· Results of	PBT and vPvB assessment
• <b>PBT:</b> Not	applicable.

• **vPvB**: Not applicable.

\*

# **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

· Dangerous components.		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas IA, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing $\leq 0,1$ % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 9004-70-0 Reg.nr.: no Reach No. availlable	nitrocellulose with water(not less than 25% water, by mass)	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226;    STOT SE 3, H336	2.5-<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-<5%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-<5%
		ontd. on page

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol diverse Farbtoene NC Spezial

	(Co	ontd. of page 2
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol 🚸 Flam. Liq. 2, H225; 🐠 Eye Irrit. 2, H319	2.5-<5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 7397-62-8 EINECS: 230-991-7 Reg.nr.: 01-2119514685-36-xxxx	butyl glycollate � Repr. 2, H361; � Eye Dam. 1, H318	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

 $\cdot$  4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

• 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

GB

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol diverse Farbtoene NC Spezial

(Contd. of page 3)

• *Information about fire - and explosion protection:* Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

• 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

	Ingredients with limi	t values that require	monitoring at the workplace:
--	-----------------------	-----------------------	------------------------------

67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

106-97-8 butane (containing  $\leq 0,1$  % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

#### 1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV

Ingredients with biological limit values:
 1330-20-7 xylene, mixture of isomers
 BMGV 650 mmol/mol creatinine
 Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

(Contd. on page 5)

<sup>-</sup> GB

Printing date 23.11.2021

Revision: 23.11.2021

#### Trade name: Aerosol diverse Farbtoene NC Spezial

(Contd. of page 4)

#### • Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

• Protection of hands:



The prep

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- $\cdot$  For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- *butyl rubber*, 0,7mm • **Eye protection:**
- Safety glasses



Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical a	nd chemical properties	
· General Information		
· Appearance:		
Form:	Aerosol	
Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Mixture is non-polar/aprotic.	
• Change in condition Melting point/freezing point: Initial boiling point and boiling ra	Undetermined. <b>nge:</b> -44.5 °C	
· Flash point:	<0 °C	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	365 °C	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
		(Contd. on page 6)

- GB

Printing date 23.11.2021

Revision: 23.11.2021

	(Contd. of page 5
Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible. Not determined.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	13 Vol %
Vapour pressure at 20 °C:	3,600 hPa
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	84.9 %
	With propellant gas. Content given by weight.
VOC (EU)	84.94 %
Solids content:	13.2 %
9.2 Other information	No further relevant information available.

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure

May cause drowsiness or dizziness.

(Contd. on page 7)

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol diverse Farbtoene NC Spezial

(Contd. of page 6)

• STOT-repeated exposure Based on available data, the classification criteria are not met. • Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
· Class	2 5F Gases.	
· Label	2.1	
· IMDG, IATA		
· Class	2.1 Gases.	

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol diverse Farbtoene NC Spezial (Contd. of page 7) · 14.4 Packing group · ADR, IMDG, IATA Void not classified · 14.5 Environmental hazards: • Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified F-D, S-U· EMS Number: SW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information:  $\cdot ADR$ lL $\cdot$  Limited quantities (LQ) Code: E0  $\cdot$  Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 D • Tunnel restriction code · IMDG · Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity · UN "Model Regulation": UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

 $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 9)

GB

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol diverse Farbtoene NC Spezial

(Contd. of page 8)

· National regulations:

· Technical instructions (air):

 Class
 Share in %

 NK
 50-100

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

#### · Department issuing SDS: Product safety department

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives - Division 1.1 Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1

 $\cdot$  \* Data compared to the previous version altered.